

S-Cargo Construction Instructions

Step 1: Carefully cut around the outside edge of both the body section and roof section.

Step 2: Carefully make an incision along the purple lines around all four tires. The cuts should only be around the lower part of the tire.

Step 3: Carefully cut out purple section below the front bumper. You'll need to make two additional cuts to join up with the incision that runs around the tire).

Step 4: Carefully make incisions (two per flap) along the purple lines on flaps **A, B, C** and **D**.

Step 5: Fold along the body lines. There are two on the body section between the tires on the right and left sides of the car and seven along the roof section of the car. Note: the folds that make up the front and back bumpers are a bit tricky.

Step 6: Fold all of the Flaps (**A, B, C, & D**) and Tabs (**a, b, c, d • ii, iii, iv, v • I, II, III, IV, V**) at the edge of the body panel of the car.

Step 8: Insert the **a** tabs into slits in flap **A** and secure tabs in place with scotch tape or glue.

Step 9: Either tape or glue the two **I** tabs to the inside of the rear bumper (along flap **A**)

Step 10: Insert **b** tabs into flap **B** and **c** tabs into tab **C** and secure tabs in place with scotch tape or glue.

**** The next three steps are more or less identical, but I have found it helps to attach the tabs along the roof and body in three sections, roof, front window and front hood. I also suggest using double sided tape if you can find it for these tabs as the results are excellent.*

Step 11: Tabs **ii** and **II** form the seam along the roof and body of the car. The tabs should fit nicely between each other and be glued to the neighboring panel.

Sept 12: Tabs **iii** and **III** form the seam along the body and front window. Again glue or tape the tabs in place as you did in step 10

Sept 13: Tabs **iv** and **IV** form the seam along the body and hood. Again glue or tape the tabs in place as you did in step 10

Step 14: Insert the **d** tabs into flap **D**. (No need for tape or glue here as they seem to hold on their own).

Step 15: Secure the **v** tabs to the front bumper with glue or tape.

Congratulations... You should now be holding your very own CBG S-Cargo!!! Now take it somewhere interesting, take a picture and send it to The Checkerboard Guy at:

cbg@thecheckerboardguy.com



